REVIEW OF TIME-DEPENDENT FATIGUE BEHAVIOR OF STRUCTURAL ALLOYS*

W. L. GREENSTREET

*Oak Ridge National Laboratory,
P.O. Box Y, Oak Ridge, Tennessee 37830, U.S.A.*

SUMMARY

The outcome of a comprehensive study** of time-dependent fatigue behaviors of alloys at elevated temperatures is described. This study was conducted by a group of preeminent individuals to summarize and assess the current state of knowledge and to define directions for future research and development work. Structural behavior evaluation and design code rule development requirements were considered along with correlative and predictive capabilities in making the assessments and in establishing requirements for future progress.

Phenomenological approaches were considered and both crack initiation and crack propagation aspects were addressed. The investigators used frameworks that were familiar to them to bring out salient features of behaviors observed, to give prospective and coherence to these observations, and to provide logical descriptions of the phenomena involved. For prospective and continuity, attempts were made to define boundaries between crack initiation and crack propagation stages.

The time-dependent fatigue designation was adopted in recognition that many time-dependent processes, including chemical and metallurgical changes, occur and combine with inelastic strain reversals to produce fatigue behavior. Because of the many basic factors and the complexities of behavior involved, emphasis was continued on the study of uniaxial responses of materials under repeated cycle conditions. Development of correlative and predictive capabilities for such cases is a prerequisite to successfully treating more complex conditions.

It was shown that correlations and predictions can be achieved with reasonable accuracy for the uniaxial-loading, repeated-cycle case. However, material behavior tests with durations well beyond those covered by programs to date are needed to better relate test to service conditions such as those experienced by nuclear reactor components. Strain aging influences, environmental effects, and thermomechanical loading responses also require additional study.

The use of inelastic strain as a correlating variable; the importance of temperature, strain rate, and time as variables; and, in particular, the importance of wave shape are generally recognized. Difficulties arise in treating loading histories, which are more complex than repeated-cycle loadings, and in handling interactions between inelastic deformation and fatigue loading influences. Refined quantitative descriptions of damage influences (changes in state of the material) required for such treatments are unavailable.

It is shown that to advance understanding of fatigue and the governing parameters, behaviors under multiaxial loading conditions must be studied in depth. Such loading conditions significantly increase the complexity, but they feature both magnitude and directional aspects of the variables involved. This broader view is essential to properly describing these variables and, ultimately, to developing methods for treating fatigue in the generality required for improved design evaluations.

* Research sponsored for the Energy Research and Development Administration under contract with Union Carbide Corporation.

** A. E. Carden, L. F. Coffin, S. S. Manson, L. K. Severud, and W. L. Greenstreet, *Time-Dependent Fatigue of Structural Alloys—A General Assessment* (1975). ORNL-5073 (January 1977).