METHODS FOR CALCULATING RADIATION INDUCED HEAT GENERATION

A.B. CHILTON,

*Nuclear Engineering Program,
University of Illinois, Urbana, Illinois, U.S.A.*

The heat production rate at any point in a medium due to a neutron or gamma ray field existing at that point can generally be simply related to the following quantities: the flux density energy spectrum at that point; the number density of the various atomic constituents at that point; the energy-dependent atomic (microscopic) cross-sections for the various interactions possible between radiation types and nuclear species; and the kinetic energy of the resulting charged particle emissions, which are assumed to be locally transformed into thermal energy. The determination of each of these quantities is discussed.

Precise knowledge of the radiation field flux density and its energy spectrum as a function of position in most practical cases requires a rather sophisticated use of one or more of the various methods of radiation transport calculation known. A brief review of these techniques and their capabilities are made herein. Fortunately, there are approximation formulas which are adequate for engineering purposes in many cases. Such formulas are largely based on use of the "point kernel" approach, which is strictly valid only for infinite homogeneous media; however, these are usually adequate, especially for gamma rays, which are in general of greater significance than neutrons in reactor shield heating.

For gamma rays, as is well known, it is the custom to combine much of the information on atomic constituents of the medium, cross-sections for the various energy-depositing interactions, and energy of the resulting charged particles (electrons) into a coefficient which we call the "energy deposition coefficient". This presentation also makes a particularly detailed review of this concept. It reviews the fundamental basis of energy deposition coefficients and indicates how one might best choose the correct values to use for it.

Comparisons of predicted and measured heat production functions are able to be found in the literature and are briefly summarized. Discrepancies found indicate the degree of accuracy generally available with today's techniques.

DISCUSSION

C. F. BONILLA, U. S. A.

Q

Realizing that most shielding problems involve materials that are considered "homogeneous", and for which appropriate empirical attenuation factors are available, have statistical methods been developed for predicting attenuation by heterogeneous materials in terms of the attenuation by the separate components, their volume fraction, size, etc. ?

A. B. CHILTON, U. S. A.

A

Yes, methods have been developed to handle this type of problem, although they are not completely rigorous. For a summary of the state of knowledge on this particular matter, I refer you to W. R. Burrus's articles in Chapter 8 of the Engineering Compendium on Radiation Shielding, Vol. I, "Shielding fundamentals and methods", published by Springer-Verlag, New York and Berlin (1968).