



US005761772A

United States Patent [19]

[11] Patent Number: 5,761,772

Clapp et al.

[45] Date of Patent: Jun. 9, 1998

[54] SECURING AND PRESSURING SYSTEM FOR DRAFTING ROLLERS FOR AUTOMATED TEXTILE DRAFTING SYSTEM

Primary Examiner—Michael A. Neas
Attorney, Agent, or Firm—Jenkins & Wilson, P.A.

[57] ABSTRACT

[75] Inventors: Timothy G. Clapp, New Hill; Jon P. Rust, Raleigh, both of N.C.; Carlos Farrington, Guatemala, Guatemala; Dale Thomas Bowen, Timberlake, N.C.; Roger Neil Saunders, Yadkinville, N.C.; Matthew Myers Thomas, Lewisville, N.C.

An automated drafting system particularly suitable for drafting textile strands of sliver is provided. The automated drafting system includes a synchronous drive sliver drafting roller system utilizing toothed gears in the preferred embodiment operatively connecting a pair of drafting rollers with one of the rollers being directly driven by a motor to thereby cause identical rotation of both rollers. The automated drafting system also includes a system for securing and pressuring together upper and lower sliver drafting rollers wherein the lower roller of a pair of drafting rollers is preferably maintained in a fixed but rotational position while the upper roller of the pair is pressured towards the lower roller and controllably restricted as to both horizontal and vertical movement during the drafting process. A sliver autoleveling system using tongue and groove drafting rollers to sense sliver uniformity is also included in the automated drafting system utilizing linear variable differential transformers (LVDTs) to monitor vertical displacement of the upper roller of a roller pair relative to the lower roller. The automated drafting system further provides a feed-forward and feed-back autoleveling system for control of sliver drafting rollers utilizing an input sliver sensor and an output sliver sensor communicating with a computer to facilitate sliver uniformity. A draftless sliver coiler packaging system is still further provided by the automated drafting system and utilizes a sliver level sensor to controllably and automatically adjust the speed at which sliver is packaged subsequent to emergence from a variable speed sliver delivery system.

[73] Assignee: North Carolina State University, Raleigh, N.C.

[21] Appl. No.: 684,037

[22] Filed: Jul. 19, 1996

[51] Int. Cl.⁶ D01H 5/74

[52] U.S. Cl. 19/260; 19/272

[58] Field of Search 19/236, 260, 266, 19/271, 272, 267, 268, 273, 278, 261

[56] References Cited

U.S. PATENT DOCUMENTS

4,187,587	2/1980	Vignon	19/272
4,510,648	4/1985	Mori et al.	19/266
4,999,884	3/1991	Vignon	19/266
5,177,835	1/1993	Ogawa et al.	19/260

FOREIGN PATENT DOCUMENTS

1325219	5/1962	France	19/272
693252	6/1953	United Kingdom	19/272
821443	10/1959	United Kingdom	19/272
873253	7/1961	United Kingdom	19/272

7 Claims, 23 Drawing Sheets

