



US006664559B1

(12) **United States Patent**
Herr et al.

(10) **Patent No.:** **US 6,664,559 B1**
(45) **Date of Patent:** **Dec. 16, 2003**

(54) **SUPERMOLECULAR STRUCTURES AND DEVICES MADE FROM SAME**

(75) Inventors: **Daniel Joseph Christian Herr**, Chapel Hill, NC (US); **Victor Vladimirovich Zhirnov**, Raleigh, NC (US)

(73) Assignees: **Semiconductor Research Corporation**, Durham, NC (US); **North Carolina State University**, Raleigh, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/510,802**

(22) Filed: **Feb. 23, 2000**

(51) Int. Cl.⁷ **H01L 29/06; H01L 31/0288**

(52) U.S. Cl. **257/14; 257/17; 257/23; 438/309**

(58) Field of Search **257/14, 23, 17; 438/309**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,981,316 A 11/1999 Yamada et al. 438/128
6,068,698 A 5/2000 Schmidt

FOREIGN PATENT DOCUMENTS

EP 0 781 727 A1 2/1997
WO 99/13511 A2 3/1999

OTHER PUBLICATIONS

Kane, "A silicon-based nuclear spin quantum computer" Nature vol. 393 May 14, 1998 pp. 133-137.*

Vanfleet et al, "Atomic-Scale Imaging of Dopant Atom Distributions Within Silicon d-Doped Layers".*

Zhirnov et al., "On Designing Sub-70-nm Semiconductor Materials and Processes," *IEEE Transactions on Semiconductor Manufacturing*, vol. 15, No. 2, May 2002.

D. M. Eigler et al., "Positioning single atoms with a scanning tunnelling microscope", *Nature*, vol. 344 (Apr. 1990) pp 524-526.

(List continued on next page.)

Primary Examiner—Jerome Jackson

(74) *Attorney, Agent, or Firm*—Moore & Van Allen PLLC; Steven B. Phillips

(57) **ABSTRACT**

Supermolecular structures and devices made from same. Semiconductor materials and devices are manufactured and provided which use controlled, discrete distribution of and positioning of single impurity atoms or molecules within a host matrix to take advantage of single charge effects. Single-dopant pn junctions and single-dopant bipolar cells are created. Each bipolar cell can function as a bistable device or an oscillator, depending on operating temperature. The cells can be used alone or in an array to make useful devices by adding an insulating substrate and contact electrodes.

22 Claims, 14 Drawing Sheets

